

How resilient to wildland fire is your home and property? Walk around your home and answer the questions below. Then consider implementing the recommended actions as you perform maintenance and renovations in each of the three Home Ignition Zones.

## **IMMEDIATE ZONE**

0 m to 1.5 m

The Immediate Zone should be a non-combustible area that starts at the house and extends to a 1.5 metre perimeter around the home and any attachments. Treat outbuildings to the same standards as your home.

#### 1. Does the structure have acceptable fire-rated roofing material?

YES 🗌	A Class-A fire-rated roof assembly offers the best protection. Metal, asphalt, clay, and composite
NO □	rubber tiles are all options. Untreated wood shakes create a dangerous combination of combustible material and crevices for embers or sparks to accumulate and enter. Refer to manufacturers' guidelines to maintain the fire resistance of your roof.

#### 2. Are the roof and gutters non-combustible and clean of debris?

YES	
ио ⇔	and clean combustible debris, like needles and leaves, from the roof and gutters. Consider installing commercial screens or covers over gutters to reduce debris accumulation.

3. Are the eaves enclosed?			
YES NO		Open eaves create a surface for embers and radiant heat. Consider enclosing eaves with properly fitted soffits and fascia to reduce the risk of embers and heat from reaching the wooden rafters of your home.	
4. Are	the	vents non-combustible and screened?	
YES NO	_	Unscreened vents can allow embers to enter a building. With the exception of dryer vents, install non-combustible vents with 3 mm metal screening in order to limit embers from accessing your home. Ensure dryer vents are clean and operational.	
5. Is e	xter	ior siding non-combustible or ignition-resistant?	
YES NO		Some types of construction material, like vinyl siding, can melt when exposed to high temperatures allowing the fire to reach the underlying wall components and penetrate the interior of the building. Stucco, metal, brick, concrete, and fibre cement siding offer superior fire resistance.	
6. Is e	xter	ior siding free of gaps, holes, or other areas where embers can accumulate?	
YES NO		Examine your siding for locations where embers could accumulate or lodge. Be sure to fix any holes and gaps in exterior siding in order to prevent embers from igniting your home.	
7. Are	win	dows multi-pane or tempered glass?	
YES NO		Single pane glass windows are highly vulnerable to breakage from radiant heat exposures that can occur during wildland fires. Multi-pane windows are less vulnerable and tempered glass windows are least vulnerable.	
8. Are exterior doors non-combustible, or fire-rated?			
YES NO		All doors into your home should be fire-rated, or non-combustible and have a good seal. This is also true for garage doors.	
9. Are exterior walls protected with a minimum 15 cm vertical non-combustible ground-to-siding clearance?			
YES NO	_	Creating a non-combustible vertical ground-to-siding clearance can be achieved by lowering the level of the ground to expose the foundation walls. It can also be achieved by replacing the first 15 cm of combustible siding with non-combustible siding material or flashing. This will limit the risk of siding igniting as a result of ember accumulation at the base of the building.	
10. Is	the	deck/porch enclosed?	
YES NO	_	Consider enclosing the underside of the deck or porch with non-combustible sheathing, as this will act as a shield against embers. Moving combustible materials stored underneath the deck to the Extended Zone, or storing inside a FireSmart-mitigated building, will limit potential for those materials to ignite.	
11. Is the deck/porch made with fire-rated materials?			
YES NO		Non-combustible, or fire-rated deck or porch materials are ideal when it comes to reducing your wildland fire risk. A non-combustible surface should be under the deck and extend for 1.5 metres out from its perimeter.	
12. Are combustible materials and landscaping materials free from this zone?			
YES NO	_	Reduce the chance of wind-blown embers igniting materials near your home. A non-combustible surface should extend around the structure and any attachments such as decks. Creating a non-combustible surface can be as easy as clearing flammable materials and vegetation. No grass or plants of any type should be present in this zone.	

# **INTERMEDIATE ZONE**

1.5 m to 10 m

0 m to 1.5 m

1.5 m to 10 m

Elements in the Intermediate Zone are managed so they don't transmit fire to your home.

L. Is the la	awn cut to a length of	10 cm or less?			
YES □ NO ➡	Mowing and maintaining	the lawn to a height of 10	cm or less will limit flame	e intensity and/or sprea	ad.
2. Is the y	ard free of combustil	ole debris?			
YES □ NO □	combustible materials, lil	ulations of combustible de ke woodpiles, building ma or a FireSmart-mitigated b	terials, patio furniture, rec		
3. Are gar	den beds lined with (	crushed rock/decorat	ive gravel?		
YES ☐ NO 🖒	Organic mulch like bark of significantly reduce the r	or pine needles are highly isk of damage from wildla	combustible. Crushed rocl and fire.	k or decorative gravel	
4. Does la	ndscaping include fir	e-resistant plants?			
YES ☐ NO 🖒		will not easily transmit fire me surviving a wildland f		fire-resistant plants cal	n increase
5. Are con	iferous trees pruned	to a height of 2 metr	es?		
YES ☐ NO 🖒		rees quickly. Removing al es from moving into the tr		nin 2 metres from the §	ground
5. Are con	iferous trees spaced	at least 3 metres apa	rt?		
YES □ NO ➡	Spacing coniferous trees transmission.	at least 3 metres apart fro	om crown-to-crown will re	duce the risk of tree-to	o-tree fire
IMMEDI	ATE ZONE	INTERMEDIATE ZON	EXT	ENDED ZONE	

10 m to 30 m

### **EXTENDED ZONE**

10 m to 30 m

The focus in the Extended Zone is not to eliminate fire, but to reduce its intensity.

1. Ar	e all 1	firewood piles and other combustible materials located within the Extended Zone?		
		Firewood and combustibles are major fire hazards. Moving all combustible material into the Extended Zone, or into a FireSmart-mitigated building, is critical to reducing wildland fire risk.		
2. Ar	e con	iferous trees pruned to a height of 2 metres?		
YES NO		A surface fire can climb trees quickly. Removing all coniferous branches within 2 metres from the ground will help stop surface fires from moving into the treetops.		
3. Are coniferous trees spaced at least 3 metres apart?				
YES NO	_	Spacing coniferous trees at least 3 metres apart from crown-to-crown will reduce the risk of tree-to-tree fire transmission.		
4. Have accumulations of fallen branches, dry grass, and needles on the ground been removed?				
YES NO		Cleaning up accumulations of fallen branches, dry grass, and needles will reduce potential surface fuels.		
	7			



The Home Ignition Zone Self-Assessment is a great step to help you on the path to wildland fire resiliency, but there are many factors that can influence your level of preparedness! So, what else can you do to be prepared?

- Take FireSmart 101, our free online course, for a deeper dive into FireSmart and how homes ignite.
- Create an evacuation plan. Find the Last-Minute Checklist on our website.
- Contact your local FireSmart Coordinator or Representative for a professional assessment of your home or neighbourhood.
- Reach out to info@firesmartbc.ca with any questions.

